




# PREMIUM

DOOR FURNITURE


## YALE DOOR FURNITURE

- Manufactured from solid brass and finished to the highest applicable standards.
- Tested to 200,000 cycles in accordance with the British Standard for lever handles.
- To suit doors 35–44mm thick.
- Due to varying door sizes the spindle may require cutting to the correct length using a hacksaw.
- Regular cleaning with a moist cloth is the only maintenance required. *Do not use abrasive cleaners.*

### BACKPLATE HANDLES



Type A  
4 screw  
fixing



Type B  
2 screw  
fixing

### ROUND ROSE HANDLES



#### TYPE A HANDLE PACK INCLUDES

- 1 pair of handles
- 1 spindle bar
- 8 wood screws

#### TYPE B HANDLE PACK INCLUDES

- 1 pair of handles
- 1 spindle bar
- 4 wood screws for solid doors
- 2 bolt through fixings for hollow doors

#### FITTING INSTRUCTIONS

1. Insert spindle bar through the mortice latch and locate one handle over the bar.
2. Mark screw hole positions with a bradawl and remove handle.  
*For Type A handle and Type B (when used on solid doors) – go to point 4*
3. Type B handle (when used on hollow doors) – drill two 6 mm holes through the door. Locate both handles with the spindle bar through the mortice latch, insert bolt through fixings and tighten.
4. Drill pilot holes and then re-locate the handle with the spindle bar through the mortice latch. Fix to the door using the wood screws provided.
5. Locate the second handle over the spindle bar and push flush to the door. Repeat steps 2 – 4 to fix.  
*For bathroom handles ensure that the grub screw is fully tightened.*

#### HANDLE PACK INCLUDES

- 1 pair of handles
- 1 spindle bar
- 8 wood screws for solid doors
- 2 bolt through fixings for hollow doors
- 1 Allen key

#### FITTING INSTRUCTIONS

1. Remove outer rose from handle to expose holes for fixing. If you are using the bolt through fixings ensure that the bolt positions suit the latch or lock that is fitted.
2. Push the spindle bar through the mortice latch and locate one handle over the spindle bar.
3. Mark screw hole positions with a bradawl and remove handle.
4. For solid doors go to step 8 for wood screw fixing.
5. For hollow doors drill two 6mm holes through the door.
6. Locate both handles with the spindle bar through the mortice latch, insert bolt through fixings and tighten.
7. Tighten the grub screw on both handles using the Allen key provided.
8. Drill pilot holes and then relocate the handle with the spindle bar through the mortice latch. Fix to the door using the wood screws provided.
9. Tighten the grub screw on the handle using the Allen key provided.
10. To fix the second handle repeat steps 1 – 9.



### The world's favorite lock

The Meadows, Cannock Road  
Wolverhampton WV10 0RR, England  
Tel: +44 (0) 1902 364 647  
Fax: +44 (0) 1902 867 158  
[www.yale.co.uk](http://www.yale.co.uk)



Issue 1



An ASSA ABLOY Group brand

ASSA ABLOY

#### DATA

<b>TITLE</b> dfpremium_fi [front].ai
<b>PRODUCT CODE</b> Various
<b>ISSUE</b> 1
<b>DATE</b> 14/12/05
<b>CREATED BY</b> Simon McMahon

#### APPROVAL / DATES

<b>MARKETING/BRAND</b> 
<b>PACKAGING TECHNICAL</b>
<b>LEGAL/DETAIL</b>
<b>CONVERTER</b>

#### SPECIFICATION DETAILS

Paper: Width 210mm x height 297mm (A4) 80 g/m <sup>2</sup> recycled paper
--

#### COLOURS

	<b>BLACK</b>
	<b>PANTONE 368 C</b> (CUTTER: DO NOT PRINT)